



Certification Record

CUSTOMER	CLASS	FILE
Lefoo Industrial Co., Ltd. Jinsi Weiliu Road, JinSi WeiLiu Rd Economic Development Zone Yueqing City Zhejiang 325600 China	3211-06 INDUSTRIAL CONTROL EQUIPMENT-Motor Controllers - Miscellaneous	220707
Refer to Class Description for program details		

- Pressure-Regulating Switch, Models LF10-4H, LF10-1H, LF10-W, ratings as below:

Electrical ratings:

20 A	120 V ac	1.5 HP	Single-phase	DPST	30,000 cycles
12 A	240 V ac	2 HP	Single-phase	DPST	6,000 cycles
9.6 A	240 V ac	3 HP	Three-phase	DPST	6,000 cycles
8.6 A	32 V dc	1/4 HP			6,000 cycles
3.1 A	120 V dc	1/4 HP			6,000 cycles
1.6 A	240 V dc	1/4 HP			6,000 cycles

Operating pressure ratings:

Maximum open cut out: 175 psi
 Minimum close cut in: 35 psi
 Differential: 30-40 psi

Notes:

- Certified as components of CSA certified equipment and combination is to be evaluated by CSA International.
- The enclosure of this device is suitable for use in air compressor since it complies with Clause 4.2.6.2 of CAN/CSA-C22.2 No. 68-92.
- The suitability of the final enclosure of this device is to be evaluated in the end use for other applications.

- Pressure-Regulating Switch, Model LF17, LF17-W, AT02104, rated 240 V, 20 A, 3 HP, 120 V, 24 A, 2 HP, Max operating pressure 250 psi.

- Pressure Switch, Model LF15, rated 125 V ac, 20 A, 1-1/2 HP, 30,000 Cycle Endurance, 125/175 psi.

Notes:

1. Certified as components of CSA Certified equipment and combination is to be evaluated by CSA International.
2. The suitability of the final enclosure of this device is to be evaluated at the end use for other applications.

Copyright © 2008 CSA International. All rights reserved.